
Technical Data





GLASSFLO MPT SPRAY Mould Pre-treatment Spray

Glassflo MPT Spray is a dry-film blank mould pre-treatment specially formulated to remove the need for manual swabbing of moulds during start-up, so giving consistent running conditions.

Glassflo MPT Spray can also be applied to blow moulds, bottom plates, neck rings and other related equipment.

Features

- Clean, air cured, dry coating requires no baking.
- Prevents adhesion of ware to moulds.
- Promotes excellent glass distribution.
- Cost efficient through reduced mould dope usage.
- Consistent quality through even film.

Directions for Use

- 1. Ensure surfaces are clean, dry and free from oil or grease.
- 2. Apply a thin, even coat from a distance of 15-20cm.
- 3. Touch dry in approximately 1 minute.
- 4. For best results allow to cure at room temperature for 2-4 hours.
- 5. After use invert can and spray until nozzle is clear.
- 6. Lightly burnish the applied film for an excellent finish to ware.

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740 E customer-service@rocol.com www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL





ROCOL A division of ITW Ltd





BS EN ISO 9001 BS EN ISO 14001 Certificate No. FM 12448 Certificate No. EMS 67596 OHSAS 18001 Certificate No. OHS 78173 INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility. **Technical Data**

Performance you can trust



GLASSFLO MPT SPRAY

| Appearance | Thin, grey/black film |
|-------------------------|---|
| Solid Lubricant | Graphite |
| Binder | Organic resin |
| Solvent | Non-chlorinated |
| Storage | Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight |
| Pack Sizes – Part codes | 400ml - 78871 |

Date: Jan-09

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740 E customer-service@rocol.com www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of ITW Ltd





BS EN ISO 9001 Certificate No. FM 12448

BS EN ISO 14001 Certificate No. EMS 67596

OHSAS 18001 Certificate No. OHS 78173 INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.